

## DATASHEET

**PASSO-SC****GENERAL**

Art.Nr:	H-137-SC-03	Standards:	EN 12275:2013/H, EN 362:2004/B, UIAA 121
GTIN:	4030281261780	Net weight:	0.09 kg
E-class number:	40-21-07-12	Gross weight:	0.09 kg
Customs tariff number:	76169990		

# DATASHEET

## PASSO-SC

The passO HMS carabiner provides the foundation for the pinchLock and inLock. As passO-Screw (screw, incl. safety marking), passO Twist (twistlock) and passO Tri (trilock) an essential part of every climbers' rack. Gate opening 30 mm in each case. - Easy to use screw gate opening, even with gloves on - Large gate opening and wide inner space - HMS carabiner for use at belay stations, anchor points, and for Munter hitch belaying

### FEATURES

Colour:	Grey
Swivel:	No
Carabiner properties:	Corrosion resistance
Fallindicator:	No
Gate opening:	27 mm
MBS MAJOR AXIS:	22 kN
MBS GATE OPEN:	7 kN
MBS MINOR AXIS:	10 kN
Form fit:	Key Lock
Carabiner type:	Type B (EN 362:2004), Type H (EN 12275:2013)
Maximum lifetime:	30 years
Minimum temperature:	-35 °C
Maximum temperature:	45 °C
Standard ANSI:	No
UIAA compliance:	Yes
Anti-twist device:	No
Locking mechanism:	Screwgate

### MATERIAL

Material:	Aluminium
-----------	-----------